



SINCE 1975

DSC ALL STAINLESS STEEL AIR TRAP

No.11AV

MOP 28K x 260°C



- ALL SEALED STAINLESS STEEL BODY OF HIGH STRENGTH AND CORROSION RESISTANCE.
- FRICTIONLESS MECHANISM MAKES LONG SERVICE YEARS.
- INLET WITH INTEGRAL STRAINER.
- LIGHT IN WEIGHT.



No.11AV DIMENSIONS (MM). MOP(KG/CM²). WT(KG)

TRAP NO.	CONN.SE*	OUTLET	A	B	C	MOP	WT
11AV	15.20.25	15	70	188	14	30	0.6
12AV	20	15.20	100	224	22	28	1.5
13AV	25	25	114	289	30	28	3.4
16AV	50	50	190	425	0	28	10

*NPT. PT. SW. AVAILABLE

*WELDIN FLANGE AVAILABLE, CONSULT FACTORY

CONSTRUCTION OF MATERIALS

BODY	S.S. 304
	S.S. 304L
	S.S. 316
MECHANISM	STAINLESS STEEL
FLOAT	STAINLESS STEEL
SEAT&VALVE	HARDENED S.S.
STRAINER	STAINLESS STEEL
MECHANISM	STAINLESS STEEL
FLOAT	STAINLESS STEEL

COLD WATER DISCHARGE CAPACITY IN KG/HR

MOP		9K	14K	17K	28K
ORIFICE		1/8"	7/64"	38#	5/64"
Δ P .KG/CM ²	3K	480	380	250	180
	5K	590	500	390	250
	9K	800	640	550	300
	14K	-	800	660	390
	17K	-	-	680	440
	28K	-	-	-	660