




DSC STAINLESS STEEL THERMOSTATIC STEAM TRAPS

No.S72 · S72F

MOP 32K x 320°C




- DSC S72 ALL STAINLESS STEEL THERMOSTATIC STEAM TRAP FOR OPERATING PRESSURE UP TO 32KG/CM² X 320°C.
- SMALL DRIBBLE AT NO LOAD, INTERMITTENT AT LIGHT AND NORMAL LOAD, CONTINUOUS AT FULL LOAD.
- EXCELLENT CORROSION RESISTANCE.
- EXCELLENT RESISTANCE TO HYDRAULIC SHOCKS.
- DO NOT VENT AIR AND CO₂ AT STEAM TEMPERATURE.
- GOOD OPERATION AGAINST BACK PRESSURE.
- GOOD RESISTANCE TO DAMAGE FROM FREEZING
- DELAYED RESPONSIVENESS TO SLUGS OF CONDENSATE.
- SMALL COMPARATIVE PHYSICAL SIZE



No.S72 DIMENSIONS (MM). WT(KG)

No.	CONN.SE.*	A	B	C	MOP	WT
S72	15	60	45	15	32	0.35
	20	60	48	17	32	0.4

*NPT. BSPT. SW. AVAILABLE



No. S72F

No.	CONN.FE.*	A	B	C	MOP	WT
S72F	15	150	45	45	32	2.3
	20	150	50	50	32	2.5

* FLANGE SPEC CONSUT FACTORY.

CONSTRUCTION OF MATERIALS

BODY	S.S 304
	S.S 304L
	S.S 316
CAGE UNIT	STAINLESS STEEL
STRAINER	STAINLESS STEEL

CONDENSATE DISCHARGE CAPACITY IN KG/HR.

